





Technical Datasheet	PolySprint™ Conveyor Belt																												
Belt type DB-4E14		PS-012 ver.0																											
Applications <ul style="list-style-type: none"> ▪ Paper straw ▪ Bookbinding machine ▪ Postal machine ▪ Packaging machine ▪ Light duty conveyor 																													
Construction <div style="display: flex; align-items: flex-start;">  <table border="0" style="width: 70%; border-collapse: collapse;"> <tr> <td style="width: 50%; vertical-align: top;"> <table border="0" style="width: 100%;"> <tr> <td style="border-bottom: 1px solid black;">Top side</td> <td style="border-bottom: 1px solid black;">Bottom side</td> </tr> <tr> <td style="border-bottom: 1px solid black;">TPU</td> <td style="border-bottom: 1px solid black;">TPU</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Taffeta pattern</td> <td style="border-bottom: 1px solid black;">Taffeta pattern</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Blue</td> <td style="border-bottom: 1px solid black;">Blue</td> </tr> </table> <table border="0" style="width: 100%;"> <tr> <td style="border-bottom: 1px solid black;">Tension member</td> <td style="border-bottom: 1px solid black;">Splice</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Polyester</td> <td style="border-bottom: 1px solid black;">Finger</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Fabric</td> <td style="border-bottom: 1px solid black;">(10×30)</td> </tr> </table> Construction  </td> <td style="width: 50%;"></td> </tr> </table> </div>			<table border="0" style="width: 100%;"> <tr> <td style="border-bottom: 1px solid black;">Top side</td> <td style="border-bottom: 1px solid black;">Bottom side</td> </tr> <tr> <td style="border-bottom: 1px solid black;">TPU</td> <td style="border-bottom: 1px solid black;">TPU</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Taffeta pattern</td> <td style="border-bottom: 1px solid black;">Taffeta pattern</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Blue</td> <td style="border-bottom: 1px solid black;">Blue</td> </tr> </table> <table border="0" style="width: 100%;"> <tr> <td style="border-bottom: 1px solid black;">Tension member</td> <td style="border-bottom: 1px solid black;">Splice</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Polyester</td> <td style="border-bottom: 1px solid black;">Finger</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Fabric</td> <td style="border-bottom: 1px solid black;">(10×30)</td> </tr> </table> Construction 	Top side	Bottom side	TPU	TPU	Taffeta pattern	Taffeta pattern	Blue	Blue	Tension member	Splice	Polyester	Finger	Fabric	(10×30)												
<table border="0" style="width: 100%;"> <tr> <td style="border-bottom: 1px solid black;">Top side</td> <td style="border-bottom: 1px solid black;">Bottom side</td> </tr> <tr> <td style="border-bottom: 1px solid black;">TPU</td> <td style="border-bottom: 1px solid black;">TPU</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Taffeta pattern</td> <td style="border-bottom: 1px solid black;">Taffeta pattern</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Blue</td> <td style="border-bottom: 1px solid black;">Blue</td> </tr> </table> <table border="0" style="width: 100%;"> <tr> <td style="border-bottom: 1px solid black;">Tension member</td> <td style="border-bottom: 1px solid black;">Splice</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Polyester</td> <td style="border-bottom: 1px solid black;">Finger</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Fabric</td> <td style="border-bottom: 1px solid black;">(10×30)</td> </tr> </table> Construction 	Top side	Bottom side	TPU	TPU	Taffeta pattern	Taffeta pattern	Blue	Blue	Tension member	Splice	Polyester	Finger	Fabric	(10×30)															
Top side	Bottom side																												
TPU	TPU																												
Taffeta pattern	Taffeta pattern																												
Blue	Blue																												
Tension member	Splice																												
Polyester	Finger																												
Fabric	(10×30)																												
<table border="0" style="width: 100%;"> <tr> <td style="width: 33%; vertical-align: top;"> Dimensions <table border="0" style="width: 100%;"> <tr><td style="border-bottom: 1px solid black;">Width/Roll (max.)</td><td style="border-bottom: 1px solid black;">340mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Width/Endless (max.)</td><td style="border-bottom: 1px solid black;">340mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Length (max.)</td><td style="border-bottom: 1px solid black;">100m</td></tr> <tr><td style="border-bottom: 1px solid black;">Total thickness</td><td style="border-bottom: 1px solid black;">1.4mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Weight</td><td style="border-bottom: 1px solid black;">1.6 Kg/m²</td></tr> </table> </td> <td style="width: 33%; vertical-align: top;"> Properties <table border="0" style="width: 100%;"> <tr> <td colspan="2" style="border-bottom: 1px solid black;">Minimum pulley diameter</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Flexing</td> <td style="border-bottom: 1px solid black;">Finger 25mm</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Back flexing</td> <td style="border-bottom: 1px solid black;">Finger 25mm</td> </tr> </table> </td> <td style="width: 33%; vertical-align: top;"> Tensile properties <table border="0" style="width: 100%;"> <tr><td style="border-bottom: 1px solid black;">Tensile strength</td><td style="border-bottom: 1px solid black;">45N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Elongation at break</td><td style="border-bottom: 1px solid black;">13%</td></tr> <tr><td style="border-bottom: 1px solid black;">Maximum allowable tension</td><td style="border-bottom: 1px solid black;">9N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Maximum allowable elongation</td><td style="border-bottom: 1px solid black;">2.0%</td></tr> </table> </td> </tr> </table>			Dimensions <table border="0" style="width: 100%;"> <tr><td style="border-bottom: 1px solid black;">Width/Roll (max.)</td><td style="border-bottom: 1px solid black;">340mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Width/Endless (max.)</td><td style="border-bottom: 1px solid black;">340mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Length (max.)</td><td style="border-bottom: 1px solid black;">100m</td></tr> <tr><td style="border-bottom: 1px solid black;">Total thickness</td><td style="border-bottom: 1px solid black;">1.4mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Weight</td><td style="border-bottom: 1px solid black;">1.6 Kg/m²</td></tr> </table>	Width/Roll (max.)	340mm	Width/Endless (max.)	340mm	Length (max.)	100m	Total thickness	1.4mm	Weight	1.6 Kg/m ²	Properties <table border="0" style="width: 100%;"> <tr> <td colspan="2" style="border-bottom: 1px solid black;">Minimum pulley diameter</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Flexing</td> <td style="border-bottom: 1px solid black;">Finger 25mm</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Back flexing</td> <td style="border-bottom: 1px solid black;">Finger 25mm</td> </tr> </table>	Minimum pulley diameter		Flexing	Finger 25mm	Back flexing	Finger 25mm	Tensile properties <table border="0" style="width: 100%;"> <tr><td style="border-bottom: 1px solid black;">Tensile strength</td><td style="border-bottom: 1px solid black;">45N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Elongation at break</td><td style="border-bottom: 1px solid black;">13%</td></tr> <tr><td style="border-bottom: 1px solid black;">Maximum allowable tension</td><td style="border-bottom: 1px solid black;">9N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Maximum allowable elongation</td><td style="border-bottom: 1px solid black;">2.0%</td></tr> </table>	Tensile strength	45N/mm	Elongation at break	13%	Maximum allowable tension	9N/mm	Maximum allowable elongation	2.0%
Dimensions <table border="0" style="width: 100%;"> <tr><td style="border-bottom: 1px solid black;">Width/Roll (max.)</td><td style="border-bottom: 1px solid black;">340mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Width/Endless (max.)</td><td style="border-bottom: 1px solid black;">340mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Length (max.)</td><td style="border-bottom: 1px solid black;">100m</td></tr> <tr><td style="border-bottom: 1px solid black;">Total thickness</td><td style="border-bottom: 1px solid black;">1.4mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Weight</td><td style="border-bottom: 1px solid black;">1.6 Kg/m²</td></tr> </table>	Width/Roll (max.)	340mm	Width/Endless (max.)	340mm	Length (max.)	100m	Total thickness	1.4mm	Weight	1.6 Kg/m ²	Properties <table border="0" style="width: 100%;"> <tr> <td colspan="2" style="border-bottom: 1px solid black;">Minimum pulley diameter</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Flexing</td> <td style="border-bottom: 1px solid black;">Finger 25mm</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Back flexing</td> <td style="border-bottom: 1px solid black;">Finger 25mm</td> </tr> </table>	Minimum pulley diameter		Flexing	Finger 25mm	Back flexing	Finger 25mm	Tensile properties <table border="0" style="width: 100%;"> <tr><td style="border-bottom: 1px solid black;">Tensile strength</td><td style="border-bottom: 1px solid black;">45N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Elongation at break</td><td style="border-bottom: 1px solid black;">13%</td></tr> <tr><td style="border-bottom: 1px solid black;">Maximum allowable tension</td><td style="border-bottom: 1px solid black;">9N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Maximum allowable elongation</td><td style="border-bottom: 1px solid black;">2.0%</td></tr> </table>	Tensile strength	45N/mm	Elongation at break	13%	Maximum allowable tension	9N/mm	Maximum allowable elongation	2.0%			
Width/Roll (max.)	340mm																												
Width/Endless (max.)	340mm																												
Length (max.)	100m																												
Total thickness	1.4mm																												
Weight	1.6 Kg/m ²																												
Minimum pulley diameter																													
Flexing	Finger 25mm																												
Back flexing	Finger 25mm																												
Tensile strength	45N/mm																												
Elongation at break	13%																												
Maximum allowable tension	9N/mm																												
Maximum allowable elongation	2.0%																												
©Please contact Nitta if you need other dimensions.																													
<table border="0" style="width: 100%;"> <tr> <td style="width: 33%; vertical-align: top;"> Regulatory compliance <ul style="list-style-type: none"> RoHS(2011/65/EC) REACH regulation </td> <td style="width: 33%; vertical-align: top;"> Dynamic properties <table border="0" style="width: 100%;"> <tr><td style="border-bottom: 1px solid black;">Standard elongation</td><td style="border-bottom: 1px solid black;">1.0%</td></tr> <tr><td style="border-bottom: 1px solid black;">Tension after relaxation at 1.0%[*]</td><td style="border-bottom: 1px solid black;">4N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Initial tension at 2.0%</td><td style="border-bottom: 1px solid black;">9N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Tension after relaxation at 2.0%[*]</td><td style="border-bottom: 1px solid black;">6N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Operating temperature range</td><td style="border-bottom: 1px solid black;">-20~60°C</td></tr> </table> </td> <td style="width: 33%; vertical-align: top;"> Coefficient of friction <table border="0" style="width: 100%;"> <tr> <td style="border-bottom: 1px solid black;">Top vs. Steel</td> <td style="border-bottom: 1px solid black;">0.4~0.5</td> </tr> <tr> <td style="border-bottom: 1px solid black;">vs. Paper</td> <td style="border-bottom: 1px solid black;">0.5~0.6</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Bottom vs. Steel</td> <td style="border-bottom: 1px solid black;">0.4~0.5</td> </tr> <tr> <td style="border-bottom: 1px solid black;">vs. Paper</td> <td style="border-bottom: 1px solid black;">0.5~0.6</td> </tr> <tr> <td style="border-bottom: 1px solid black;">vs. Lagged pulley</td> <td style="border-bottom: 1px solid black;">0.6~0.8</td> </tr> <tr> <td style="border-bottom: 1px solid black;">vs. POM (resin)</td> <td style="border-bottom: 1px solid black;">0.4~0.6</td> </tr> </table> </td> </tr> </table>			Regulatory compliance <ul style="list-style-type: none"> RoHS(2011/65/EC) REACH regulation 	Dynamic properties <table border="0" style="width: 100%;"> <tr><td style="border-bottom: 1px solid black;">Standard elongation</td><td style="border-bottom: 1px solid black;">1.0%</td></tr> <tr><td style="border-bottom: 1px solid black;">Tension after relaxation at 1.0%[*]</td><td style="border-bottom: 1px solid black;">4N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Initial tension at 2.0%</td><td style="border-bottom: 1px solid black;">9N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Tension after relaxation at 2.0%[*]</td><td style="border-bottom: 1px solid black;">6N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Operating temperature range</td><td style="border-bottom: 1px solid black;">-20~60°C</td></tr> </table>	Standard elongation	1.0%	Tension after relaxation at 1.0% [*]	4N/mm	Initial tension at 2.0%	9N/mm	Tension after relaxation at 2.0% [*]	6N/mm	Operating temperature range	-20~60°C	Coefficient of friction <table border="0" style="width: 100%;"> <tr> <td style="border-bottom: 1px solid black;">Top vs. Steel</td> <td style="border-bottom: 1px solid black;">0.4~0.5</td> </tr> <tr> <td style="border-bottom: 1px solid black;">vs. Paper</td> <td style="border-bottom: 1px solid black;">0.5~0.6</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Bottom vs. Steel</td> <td style="border-bottom: 1px solid black;">0.4~0.5</td> </tr> <tr> <td style="border-bottom: 1px solid black;">vs. Paper</td> <td style="border-bottom: 1px solid black;">0.5~0.6</td> </tr> <tr> <td style="border-bottom: 1px solid black;">vs. Lagged pulley</td> <td style="border-bottom: 1px solid black;">0.6~0.8</td> </tr> <tr> <td style="border-bottom: 1px solid black;">vs. POM (resin)</td> <td style="border-bottom: 1px solid black;">0.4~0.6</td> </tr> </table>	Top vs. Steel	0.4~0.5	vs. Paper	0.5~0.6	Bottom vs. Steel	0.4~0.5	vs. Paper	0.5~0.6	vs. Lagged pulley	0.6~0.8	vs. POM (resin)	0.4~0.6		
Regulatory compliance <ul style="list-style-type: none"> RoHS(2011/65/EC) REACH regulation 	Dynamic properties <table border="0" style="width: 100%;"> <tr><td style="border-bottom: 1px solid black;">Standard elongation</td><td style="border-bottom: 1px solid black;">1.0%</td></tr> <tr><td style="border-bottom: 1px solid black;">Tension after relaxation at 1.0%[*]</td><td style="border-bottom: 1px solid black;">4N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Initial tension at 2.0%</td><td style="border-bottom: 1px solid black;">9N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Tension after relaxation at 2.0%[*]</td><td style="border-bottom: 1px solid black;">6N/mm</td></tr> <tr><td style="border-bottom: 1px solid black;">Operating temperature range</td><td style="border-bottom: 1px solid black;">-20~60°C</td></tr> </table>	Standard elongation	1.0%	Tension after relaxation at 1.0% [*]	4N/mm	Initial tension at 2.0%	9N/mm	Tension after relaxation at 2.0% [*]	6N/mm	Operating temperature range	-20~60°C	Coefficient of friction <table border="0" style="width: 100%;"> <tr> <td style="border-bottom: 1px solid black;">Top vs. Steel</td> <td style="border-bottom: 1px solid black;">0.4~0.5</td> </tr> <tr> <td style="border-bottom: 1px solid black;">vs. Paper</td> <td style="border-bottom: 1px solid black;">0.5~0.6</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Bottom vs. Steel</td> <td style="border-bottom: 1px solid black;">0.4~0.5</td> </tr> <tr> <td style="border-bottom: 1px solid black;">vs. Paper</td> <td style="border-bottom: 1px solid black;">0.5~0.6</td> </tr> <tr> <td style="border-bottom: 1px solid black;">vs. Lagged pulley</td> <td style="border-bottom: 1px solid black;">0.6~0.8</td> </tr> <tr> <td style="border-bottom: 1px solid black;">vs. POM (resin)</td> <td style="border-bottom: 1px solid black;">0.4~0.6</td> </tr> </table>	Top vs. Steel	0.4~0.5	vs. Paper	0.5~0.6	Bottom vs. Steel	0.4~0.5	vs. Paper	0.5~0.6	vs. Lagged pulley	0.6~0.8	vs. POM (resin)	0.4~0.6					
Standard elongation	1.0%																												
Tension after relaxation at 1.0% [*]	4N/mm																												
Initial tension at 2.0%	9N/mm																												
Tension after relaxation at 2.0% [*]	6N/mm																												
Operating temperature range	-20~60°C																												
Top vs. Steel	0.4~0.5																												
vs. Paper	0.5~0.6																												
Bottom vs. Steel	0.4~0.5																												
vs. Paper	0.5~0.6																												
vs. Lagged pulley	0.6~0.8																												
vs. POM (resin)	0.4~0.6																												
Features <ul style="list-style-type: none"> Antistatic Roller bed Easy splice with NITTA tool <p style="text-align: right; font-size: small;">*After 200hrs running-in</p>																													